


This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended) A method for processing a feed ~~mixture of two or more gases wherein said feed mixture contains at least one C₅₊ hydrocarbon component~~, said method comprising:


(a) providing a selectively permeable membrane wherein said membrane comprises a first side and a second side~~[[;]]~~ .

(b) ~~—~~wherein said membrane further comprises at least one polymer or copolymer comprising a repeating units unit of formula (I):




(I)


in which R₂ is a moiety having a composition ~~selected from the group of consisting of formula (A), formula (B), formula (C), and mixtures thereof,~~



(A)




(B)




(C)


in which Z is a moiety having a composition ~~selected from the group consisting of formula (L), formula (M), formula (N) and mixtures thereof,~~



~~(L)~~




(M)




~~(N)~~


and in which R₁ is a moiety having a composition selected from the group consisting of formula (Q), formula (S), formula (T), and mixtures thereof,



(Q)



(S)




(T);

- (e b) contacting the said first side of the said membrane with said a gaseous feed mixture of at least two or more gas components;
- (~~d~~ c) causing at least one component of the said gaseous feed mixture to selectively permeate through the membrane, thereby forming on the said second side of the said membrane a permeate composition which has a concentration of at least one component that is greater than the concentration of the said gaseous feed mixture;
- (e d) removing from the said second side of the said membrane the said permeate composition; and

(f e) withdrawing from the said first side of the said membrane a composition which has a concentration of at least one component that is less than the concentration of the said gaseous feed mixture.


Claim 2 (currently amended) ~~The method of claim 1,~~ A method for processing a feed, said method comprising:

(a) providing a selectively permeable membrane wherein said membrane comprises a first side and a second side, wherein said membrane further comprises at least one polymer or copolymer comprising a repeating unit of formula (I):




(I)


in which R₂ is a moiety having a composition selected from the group of consisting of formula (A), formula (B), formula (C), and mixtures thereof,



(A)




(B)




(C)


in which Z is a moiety having a composition selected from the group consisting of formula (L), formula (M), formula (N) and mixtures thereof,



(L)




(M)




(N)


wherein R₁ is a moiety having a composition selected from the group consisting of formula (Q), formula (S), formula (T):



(Q)



(S)



(T)

and mixtures thereof

- (b) contacting said first side of said membrane with said gaseous feed mixture of at least two or more gas components;
- (c) causing at least one component of said gaseous feed mixture to selectively permeate through said membrane, thereby forming on said second side of said membrane a permeate composition with a concentration of said component or components that is greater than a concentration of said component or components in said gaseous feed mixture;
- (d) removing from said second side of said membrane said permeate composition; and
- (e) withdrawing from said first side of said membrane a composition which has a concentration of said component or components that is less

than a concentration of said component or components in said gaseous feed mixture.

Claim 3 (currently amended) The method of claim 1, wherein ~~the~~ said gaseous feed mixture further comprises at least hydrogen and methane.

Claim 4 (currently amended) The method of claim 1, wherein ~~the~~ said gaseous feed mixture further comprises at least carbon dioxide and methane.


Claim 5 (currently amended) The method of claim 1, wherein ~~the~~ said gaseous feed mixture further comprises at least nitrogen and methane.

Claim 6 (currently amended) The method of claim 1, further comprising the steps of repeating steps (a)-(d ~~e~~) continuously or nearly continuously for at least about 200 hours of operation, wherein after about 200 hours of operation, ~~the~~ said membrane exhibits a permeance for ~~the~~ said at least one gas component ~~more permeable-gas that is at least about 70 % of the permeance~~ of said at least one gas component at an initial time of use.

Claim 7 (original) The method of claim 1, wherein said membrane comprises a composite hollow fiber membrane comprising a supporting core layer and a gas-separating sheath layer.

Claim 8 (currently amended) The method of claim 1, wherein ~~the~~ said gaseous feed mixture further comprises at least one olefin and at least one paraffin, and wherein at least one olefin is separated from said mixture.

Claim 9 (currently amended) The method of claim 4 2, wherein ~~the~~ said repeating ~~units~~ unit of formula (I) ~~comprise~~ comprises repeating units of formula (Ia):



(Ia)


wherein R_1 is a moiety as defined above.

Claim 10 (canceled)


Claim 11 (canceled)

Claim 12 (currently amended) ~~The method of claim 2,~~ A method for processing a feed, said method comprising:

(a) providing a selectively permeable membrane wherein said membrane comprises a first side and a second side, and wherein said membrane further comprises at least one polymer or copolymer comprising
wherein the repeating units of formula (I) comprise a plurality of repeating
units having a composition of formula (Ia) and ~~repeating units having a~~
composition of formula (Ib):




(Ia)




(Ib)


wherein R₁ is a moiety having a composition selected from the group consisting of formula (Q), formula (S), formula (T):



(Q)



(S)



(T)

and mixtures thereof,

wherein units of formula (Ib) comprise about 1 – 99% of the total of said repeating units of formulas (Ia) and (Ib)_i

(b) contacting said first side of said membrane with said gaseous feed mixture of at least two or more gas components;

(c) causing at least one component of said feed mixture to selectively permeate through said membrane, thereby forming on said second side of said membrane a permeate composition which has a concentration of said component or components that is greater than a concentration of said component or components in said feed mixture;

(d) removing from said second side of said membrane said permeate composition; and

(e) withdrawing from said first side of said membrane a composition which has a concentration of said component or components that is less than a concentration of said component or components in said gaseous feed mixture.


Claim 13 (currently amended) The method of claim 12, wherein R₁ is comprised of formula (Q) in about 1-99% of the said repeating units, and wherein R₁ is comprised of formula (S) in a complementary amount so as to total 100%.

Claim 14 (currently amended) The method of claim 12, in which ~~the moiety~~ R₁ has a composition of formula (Q) in about 20% of ~~the~~ said repeating units, wherein ~~the moiety~~ R₁ has a composition of formula (S) in about 80% of ~~the~~ said repeating units, and wherein said repeating units of formula (Ib) comprise about 40% of the total of said repeating units of formulas (Ia) and (Ib) in formula (I).

Claim 15 (currently amended) The method of claim 1, wherein said gaseous feed mixture comprises at least one C₅₊ hydrocarbon component, and wherein said at least one C₅₊ hydrocarbon component condenses in liquid form on ~~the~~ said first side of ~~the~~ said membrane and wherein said first side comprises the feed side of ~~the~~ said membrane.


Claim 16 (currently amended) A method for processing a feed ~~mixture of two or more gases wherein said mixture contains at least one C₅₊ hydrocarbon component~~, said method comprising:

- (a) providing a gas separation membrane having a first side and a second side, said membrane comprising a blend of at least one polymer of a Type 1 copolyimide and at least one polymer of a Type 2 copolyimide in which the Type 1 copolyimide comprises a repeating units unit of formula (I):




(I)


in which R₁ is a moiety having a composition selected from the group consisting of formula (Q), formula (S), formula (T), and mixtures thereof,



(Q)




(S)




(T)


and R_2 is a moiety having a composition selected from the group of consisting of formula (A), formula (B), formula (C), and mixtures thereof.



(A)




(B)




(C)


in which Z is a moiety having a composition selected from the group consisting of formula (L), formula (M), formula (N) and mixtures thereof:



(L)




(M)




(N)

in which the Type 2 copolyimide comprises the a Type 2 repeating units unit of formulas (IIa) and (IIb)




(IIa) IIa




(IIb)

in which Ar is a moiety having a composition selected from the group consisting of formula (U), formula (V):



(U)




(V)

and mixtures thereof, in which X, X₁, X₂, X₃ are selected independently from the group consisting of hydrogen and alkyl groups having 1 to 6 carbon atoms, and in which at least two of X, X₁, X₂, X₃ in each of the formula (U) and the formula (V) are an alkyl group.

in which Ar' is an aromatic diamine moiety, and

in which R_a and R_b are each selected independently from the group consisting of formula (A), formula (B), formula (C), formula (D).



and mixtures thereof, wherein Z is as defined above;

- (b) contacting the said first side of the said membrane with a feed mixture comprising at least one C_{5+} hydrocarbon component;
- (c) causing ~~one~~ at least one component of the said feed mixture to selectively permeate through the said membrane, thereby forming on the said second side of the said membrane a permeate composition which has a concentration of said ~~one~~ component or components greater than a concentration of said component or components in that of the said feed mixture;
- (d) removing from the said second side of the said membrane the said permeate composition; and
- (e) withdrawing from the said first side of the said membrane a composition which has a concentration of the said ~~one~~ component or components that is less than a concentration of said component or components in that of the said feed mixture.

Claim 17 (canceled)

Claim 18 (canceled)

Claim 19 (currently amended) The method of claim 16, wherein the a ratio of Type 1 polymer to Type 2 polymer in the blend is at least about 1.0.

Claim 20 (currently amended) The method of claim 16, wherein the said feed mixture comprises at least hydrogen and methane.

Claim 21 (currently amended) The method of claim 16, wherein the said feed mixture comprises at least carbon dioxide and methane.

Claim 22 (currently amended) The method of claim 16, wherein the said feed mixture comprises at least nitrogen and methane.

Claim 23 (currently amended) The method of claim 16, wherein the said feed mixture is selected from the group consisting of carbon dioxide; carbon monoxide; sulfide gases; hydrogen sulfide; paraffins; iso-paraffins; olefins; ozone; argon; chlorine; hydrogen; methane; nitrogen; carbon monoxide; propylene; propane; hexane; and a combination mixtures thereof.


Claim 24 (currently amended) The method of claim 16, further comprising the step of repeating steps (a)-(d e) continuously or nearly continuously for at least about 200 hours of operation, wherein after about 200 hours of operation, the membrane exhibits a permeance for ~~the more permeable gas~~ said component or components that is at least about 70% of the permeance of said component or components at an initial time of usage.

Claim 25 (currently amended) The method of claim 16, wherein the said membrane comprises a composite hollow fiber membrane comprised of a supporting core layer and a gas-separating sheath layer.

Claim 26 (currently amended) The method of claim 16, wherein at least one of said at least one C₅+ hydrocarbon components condenses in liquid form on ~~the~~ said first side of the membrane and wherein said feed mixture is fed to said first side comprises the feed side of the said membrane.


Claim 27 (currently amended) A method for processing a feed ~~mixture of two or more gases wherein said feed mixture contains at least one C₅+ hydrocarbon component~~, said method comprising:

- (a) providing a composite selectively permeable membrane comprising a corelayer with at least a first side and a second side and a gas-separating sheath layer wherein the said core layer comprises a polymer or copolymer comprising a repeating units unit of formula (I):




(I)


in which R₂ is a moiety having a composition selected from the group of consisting of formula (A), formula (B), formula (C) and mixtures thereof,



(A)




(B)




(C)


in which Z is a moiety having a composition selected from the group consisting of formula (L), formula (M), formula (N) and mixtures thereof; and



(L)




(M)




(N)


R₁ is a moiety having a composition selected from the group consisting of formula (Q), formula (S), formula (T), and mixtures thereof:



(Q)



(S)




(T)

- (b) contacting at least ~~the~~ said first side of ~~the~~ said membrane with a gaseous feed mixture of at least two or more gas components, wherein said gaseous feed mixture comprises at least one C₅₊ hydrocarbon component;
- (c) causing at least one component of ~~the~~ said gaseous feed mixture to selectively permeate through ~~the~~ said membrane, thereby forming on ~~the~~ said second side of the membrane a permeate composition which has a concentration of at least one component that is greater than the concentration of ~~the~~ said gaseous feed mixture;
- (d) removing from ~~the~~ said second side of ~~the~~ said membrane ~~the~~ said permeate composition; and

(e) withdrawing from the said first side of the said membrane a composition which has a concentration of at least one component that is less than the concentration of said component or components in the said gaseous feed mixture.


Claim 28 (currently amended) The method of claim 27, in which the said repeating units unit of formula (I) ~~comprise~~ comprises repeating units of formula (Ia):



(Ia)


Claim 29 (currently amended) The method of claim 28, in which R₁ is comprised of formula (Q) in about 16% of the said repeating units, formula (S) in about 64% of the said repeating units, and formula (T) in about 20% of the said repeating units.

Claim 30 (currently amended) The method of claim 27, in which the said repeating units unit of formula (I) ~~comprise~~ comprises repeating units of formula (Ib):



(Ib)

Claim 31 (currently amended) The method of claim 27, in which the said repeating units of formula (I) comprise a plurality of repeating units having a composition of formula (Ia) and ~~repeating units having~~ a composition of formula (Ib):



wherein units of formula (Ib) comprise about 1 – 99% of the total of said repeating units of formulas (Ia) and (Ib), and in which R₁ is comprised of formula (Q) in about 1-99% of the said repeating units, and wherein R₁ is comprised of formula (S) in a complementary amount so as to total 100%.

Claim 32 (currently amended) The method of claim 31, in which ~~the moiety~~ R₁ has a composition of formula (Q) in about 20% of the said repeating units, and wherein ~~the moiety~~ R₁ has a composition of formula (S) in about 80% of the said repeating units, and wherein repeating units of formula (Ib) comprise about 40% of the total of said repeating units of formulas (Ia) and (Ib) in formula (I).

Claim 33 (currently amended) The method of claim 27, wherein the driving force for separation comprises a pressure gradient across the said membrane of about 0.69 MPa to about 13.8 MPa.

Claim 34 (currently amended) The method of claim 27, wherein said membrane provided is contained in a permeator, and wherein ~~comprises~~ at least two said permeators are provided.

Claim 35 (currently amended) The method of claim 34, wherein ~~two~~ said permeators are used to separate or concentrate said ~~gas~~ gaseous feed mixture and wherein ~~the~~ an average performance of said permeators is about 3 GPU to about 30 GPU carbon dioxide permeance.

Claim 36 (currently amended) The method of claim 34, wherein ~~two~~ said permeators are used to separate or concentrate said ~~gas~~ gaseous feed mixture and wherein ~~the~~ a carbon dioxide/nitrogen selectivity ratio is about 10 to about 25.